查询APT10021JFLL供应商

APT10021JFLL

1000V 37A 0.210Ω

POWER MOS 7™ FREDFET

Power MOS 7™ is a new generation of low loss, high voltage, N-Channel enhancement mode power MOSFETS. Both conduction and switching losses are addressed with Power MOS 7™ by significantly lowering $R_{DS(ON)}$ and Q_g. Power MOS 7™ combines lower conduction and switching losses along with exceptionally fast switching speeds inherent with APT's patented metal gate structure.



ISOTOP®



- **Lower Input Capacitance**
- **Lower Miller Capacitance**
- **Lower Gate Charge, Qg**
- **Increased Power Dissipation**
- **Easier To Drive**
- **Popular SOT-227 Package**
- **FAST RECOVERY BODY DIODE**

MAXIMUM RATINGS All Ratings: T_C = 25°C unless otherwise specified.

Symbol	Parameter	APT10021JFLL	UNIT
V_{DSS}	Drain-Source Voltage	1000	Volts
I_D	Continuous Drain Current @ T_C = 25°C	37	Amps
I_{DM}	Pulsed Drain Current ①	148	
V_{GS}	Gate-Source Voltage Continuous	±30	Volts
V_{GSM}	Gate-Source Voltage Transient	±40	
P_D	Total Power Dissipation @ T_C = 25°C	690	Watts
	Linear Derating Factor	5.52	W/°C
T_J,T_{STG}	Operating and Storage Junction Temperature Range	-55 to 150	°C
T_L	Lead Temperature: 0.063" from Case for 10 Sec.	300	
I_{AR}	Avalanche Current ① (Repetitive and Non-Repetitive)	37	Amps
E_{AR}	Repetitive Avalanche Energy ①	50	mJ
E_{AS}	Single Pulse Avalanche Energy ④	3600	

ADVANCE TECHNICAL INFORMATION

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Characteristic / Test Conditions	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-Source Breakdown Voltage (V_{GS} = 0V, I_D = 250μA)	1000			Volts
$I_{D(on)}$	On State Drain Current ② (V_{DS} > $I_{D(on)}$ x $R_{DS(on)}$ Max, V_{GS} = 10V)	37			Amps
$R_{DS(on)}$	Drain-Source On-State Resistance ② (V_{GS} = 10V, 0.5 $I_{D[Cont.]}$)			0.210	Ohms
I_{DSS}	Zero Gate Voltage Drain Current (V_{DS} = V_{DSS}, V_{GS} = 0V)			250	μA
	Zero Gate Voltage Drain Current (V_{DS} = 0.8 V_{DSS}, V_{GS} = 0V, T_C = 125°C)			1000	
I_{GSS}	Gate-Source Leakage Current (V_{GS} = ±30V, V_{DS} = 0V)			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = 5mA)	3		5	Volts

CAUTION: These Devices are Sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

APT Website - http://www.advancedpower.com

USA 405 S.W. Columbia Street Bend, Oregon 97702-1035 Phone: (541) 382-8028 FAX: (541) 388-0364

EUROPE Chemin de Magret F-33700 Merignac - France Phone: (33) 5 57 92 15 15 FAX: (33) 5 56 47 97 61

050-7035 Rev A 8-2001

DYNAMIC CHARACTERISTICS

APT10021JFLL

Symbol	Characteristic	Test Conditions	MIN	TYP	MAX	UNIT
C_{iss}	Input Capacitance	V_{GS} = 0V		9980		pF
C_{oss}	Output Capacitance	V_{DS} = 25V		1650		
C_{rss}	Reverse Transfer Capacitance	f = 1 MHz		328		
Q_g	Total Gate Charge ③	V_{GS} = 10V		382		nC
Q_{gs}	Gate-Source Charge	V_{DD} = 0.5 V_{DSS}		59		
Q_{gd}	Gate-Drain ("Miller") Charge	I_D = I_D [Cont.] @ 25°C		254		
$t_d(on)$	Turn-on Delay Time	V_{GS} = 15V		18		ns
t_r	Rise Time	V_{DD} = 0.5 V_{DSS}		9		
$t_d(off)$	Turn-off Delay Time	I_D = I_D [Cont.] @ 25°C		46		
t_f	Fall Time	R_G = 0.6Ω		11		

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Symbol	Characteristic / Test Conditions		MIN	TYP	MAX	UNIT
I_S	Continuous Source Current (Body Diode)				37	Amps
I_{SM}	Pulsed Source Current ① (Body Diode)				148	
V_{SD}	Diode Forward Voltage ② (V_{GS} = 0V, I_S = -I_D [Cont.])				1.3	Volts
$^{dv}/_{dt}$	Peak Diode Recovery $^{dv}/_{dt}$ ⑤				18	V/ns
t_{rr}	Reverse Recovery Time (I_S = -I_D [Cont.], $^{di}/_{dt}$ = 100A/µs)	T_j = 25°C			300	ns
		T_j = 125°C			600	
Q_{rr}	Reverse Recovery Charge (I_S = -I_D [Cont.], $^{di}/_{dt}$ = 100A/µs)	T_j = 25°C		1.8		µC
		T_j = 125°C		7.4		
I_{RRM}	Peak Recovery Current (I_S = -I_D [Cont.], $^{di}/_{dt}$ = 100A/µs)	T_j = 25°C		16		Amps
		T_j = 125°C		30		

THERMAL CHARACTERISTICS

Symbol	Characteristic	MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction to Case			0.18	°C/W
$R_{\theta JA}$	Junction to Ambient			40	

① Repetitive Rating: Pulse width limited by maximum junction temperature.

② Pulse Test: Pulse width < 380 µs, Duty Cycle < 2%

③ See MIL-STD-750 Method 3471

④ Starting T_j = +25°C, L = 5.26mH, R_G = 25Ω, Peak I_L = 37A

⑤ $^{dv}/_{dt}$ numbers reflect the limitations of the test circuit rather than the device itself. $I_S \le -I_{D[Cont.]}$ $^{di}/_{dt} \le 700A/\mu s$ $V_R \le V_{DSS}$ $T_J \le 150°C$

APT Reserves the right to change, without notice, the specifications and information contained herein.

ADVANCE TECHNICAL INFORMATION

SOT-227 (ISOTOP®) Package Outline



Dimensions in Millimeters and (Inches)

APT's devices are covered by one or more of the following U.S.patents: 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058